

VARIMAT 300



To the product



Technical data		
Voltage	230 V; 400 V	
Frequency	50/60 Hz	
Power	3680-5700 W	
Speed	1.0-10.0 m/min	3.28-32.81 ft/min
Temperature	100-620 °C	212.0-1148.0 °F
Air volume adjustable	Yes	
Welding nozzle / seam width	40 mm	1.57 in
Welding materials	ECB; EPDM; EVA; FPO; PIB; PO; PVC; PVC-P; TPE; TPO; TPU	
LQS	No	
Brushless blower motor	No	
Brushless drive motor	Yes	
Length	605.0 mm	23.81 in
Width	335.0 mm	13.18 in
Height	373.0 mm	14.68 in
Weight	37.5 kg	82.67 lb
Power cable length	5.0 m	16.4 ft
Approvals	CB Certification; CE; UKCA	
Protection class	I	
Country of origin	CH	



VARIMAT 300

Scope of delivery

Welding plate; Wire brush, stainless steel; Nozzle adjustment gauge VARIMAT 700/500/300; Screwdriver, Torx T20; Allen wrench 4 mm; Rolling Transport Case VARIMAT 700/500/300

Product items

173.184	VARIMAT 300, 400V/5700W, 40mm, CEE 5/16
173.185	VARIMAT 300, 230V/3680W, 40mm, EU plug
173.186	VARIMAT 300, 230V/3680W, 40mm, CEE 3/16
174.616	VARIMAT 300, 230V/3680W, 40mm, °F, w/o plug